



# INNBOX G64

## GPON FTTH Home Gateway

**By introducing latest fiber GPON access technology, Innbox brings carrier class high-end networking solution for advanced triple play services. Complying with the latest ITU-T G.984 GPON standard, Innbox GPON FTTH Home Gateway G64 is designed for service providers to meet the demand for desired high-speed connections, offering rates up to 2.5Gbps downstream and up to 1.25Gbps upstream. Innbox G64 is designed for indoor applications, presenting lower cost alternative to outdoor solutions, significantly lowering CAPEX with advanced FTTH deployments.**

The FTTH Home Gateway Innbox G64 supports delivery of all triple play services: internet data, Voice over IP (VoIP) and IP video including bandwidth consuming HDTV. For packet based terminal devices the Innbox G64 GPON Home Gateway provides up to four Gigabit Ethernet ports as well as a wireless access point of standard 802.11N that brings relief to those troublesome wirings. Moreover it offers two ports for telephony services using Voice over IP technology compatible with SIP environments. With embedded NAT, firewall and IP sharing technology Innbox G64 Home Gateway delivers secure broadband Internet access to be shared by all connected clients. In addition to all local connection options, two USB2.0 host ports are available to enable value-added features such as file server, FTP server, printer server, hub or external 3G/LTE modem connectivity. The FTTH GPON Home Gateway Innbox G64 also embeds special Quality of Experience (QoE) monitoring client which enables on-line evaluation of data path all the way to HGW, which can reflect in significant lower OPEX of operator.

## Key Features and Benefits >

ITU G.984 GPON compliant

Powerfull Full Gigabit Home Gateway engine for offering 3Play services

Multiple interface options: Gigabit Ethernet, FXS for POTS, WLAN 802.11n, USB2.0, 3G/LTE (for backup connectivity)

Real 3Play proven Home Gateway to provide multiple HDTV IP streams

Fully featured Router and Firewall, secure wireless transmitting and authentication

Line rate routing performance

Embedded QoE monitoring solution

Battery backup for lifeline services

Optional Fiber Termination Unit

K.21 overvoltage protection on all wired interfaces

## TECHNICAL SPECIFICATIONS

Note: some features are hardware dependant;  
some feature may not be included in dedicated software release.

### WAN Specifications

- Full ITU-T G.984 compliance
- SC/APC connector
- Tx (1.25Gbps upstream data rate)
  - 1310nm (Launch Power: 0,5 to +5 dBm)
- Rx (2.5Gbps downstream data rate)
  - 1490nm (Input power overload: -8 dBm)

### GPON

- Fully ITU-T G.984 compliant framing
- Multiple T-CONTs per device
- Multiple GEM Ports per device
- Activation with automatic discovered SN and password in conformance with ITU-T
- AES-128 Decryption with key generation and switching
- FEC (Forward Error Correction)
- 802.1p mapper service profile on U/S
- Support for Multicast GEM Port

### Bandwith/Distance

- Compliant with ITU-T G.984.5, Class B+
  - APD receiver and DFB transmitter
  - 0.5~+5dBm launch power, -27 dBm sensitivity and -8dBm overload

### Local Interfaces

- 4 ports Gigabit Ethernet 10/100/1000Base-TX (RJ-45 jack)
  - Automatic MDI/MDIX crossover, Auto-negotiation and speed auto-sensing, Half/Full duplex support
  - Meets IEEE 802.3 specifications
  - Support for 802.1Q and 802.1p VLAN
- Internal 802.11bgn WLAN Access Point, 2x2 MIMO, 2.4GHz, internal antennas
- 2 ports FXS (RJ-11) for POTS connection
- 1 ports USB 2.0 with host connector (2 optional)

### Bridging

- Ethernet bridging/switching per IEEE 802.1D/802.1Q
- Traffic management (priority queuing and traffic shaping)
- QoS with support for IEEE 802.1p + DSCP
- Per port IEEE 802.1Q VLAN ID processing
- VLAN tagging/untagging
- IGMP v2/v3 Snooping
- Automatic MAC learning and aging
- Unlimited # of MAC addresses for OMCI-configured flows
- Support for up to 4096 MAC addresses for RG traffic flows
- Broadcast storm control

### IP Routing

- IP routing: RIP1, RIP2, and static routing
- RFC2684 (RFC1483) Routed
- PPPoE client
- PPPoE pass-through
- DHCP client, server & relay (RFC2131)
- (D)DNS client & relay
- IP Multicast IGMP Proxy
- RTP Proxy PPPoE
- NAT/NAPT with port forwarding

### USB2.0 applications

- File server (by using USB2.0 disk, flash or HDD), DLNA
- Printer server
- Hub connectivity
- 3G or LTE modem (optional)

### Wireless

- WiFi Protected Setup (WPS)
- WEP: 64 or 128 bits key length
- WPA/WPA2 (Wi-Fi Protected Access) in PSK mode or using EAP with RADIUS
- Access control list based on MAC address

### Security & QoS

- NAT (RFC3022) basic Firewall support with extensive ALG support
- Firewall with well known applications setup
- URL filtering
- Time Scheduler (parental control)
- DMZ/IP pass-through
- VPN pass-through
- ToS/DSCP to CoS mapping
- Bandwidth reservation
- Voice traffic prioritization

### Configuration & Network Management

- OMCI
- UPnP / DLNA
- Simple port configuration
- Telnet for local or remote management
- WEB for firmware upgrade and configuration
- WEB-based configuration and management (multi-level GUI)
- TR-069 data-frame model support, including TR-098, TR-104 and TR-106
- IxRave QoE monitoring client of Ixia® (optional) and TR-143 tools
- IPERF and TCP dump (optional)
- Buttons: WLAN, WPS, Reset

### Voice support

- Voice compressions G.711 (64kbps, A-law, u-law PCM), G.729ab (8kbps) - optional
- Line Echo Cancellation G.168 with configurable tail
- Voice Activity Detection (VAD), Comfort Noise Generation (CNG)
- Adaptive jitter buffer and Packet Loss Compensation (PLC)
- DTMF (tone) dialing, modem/fax tone detection and pass-through
- Supports SIPv2 (RFC 3261), RTP (RFC3550)
- Supports RTP Profile for Audio and Video Conferences with minimal control (RFC 3551)
- Supports RTP payload for DTMF events (RFC2833)
- Caller ID (Type-1 and 2)
- T.38 Fax

### Power

- External 115-230 VAC, 50 - 60 Hz, 12VDC 1.5A
- UPS connector
- Power consumption, less than 15W

### Physical dimensions

- 141mm x 243mm x 35mm, weight 0.45 kg

### Environment

- Operating Temperature: 5°C ~ 40°C, Humidity: 5% ~ 85% (non condensing), compliant with ETSI 300 019-1 -3, Class 3.1
- Storage Temperature: -25°C ~ +55°C, Humidity: 10% ~ 95% (non condensing), compliant with ETSI 300 019-1 -1, Class 1.2

### Optional accessories

- Fiber Termination Unit (FTU)
- Uninterruptible Power Supply (UPS)
- 3G USB modem, Innbox WU520
- LTE USB modem, Coming soon...

### Certification

- CE, CB, RoHS compliant

